

PRODUCT DATA SHEET

Revision Date: 13/01

ATUREX[®] 350

Liquid Polyamide Resin

ATUREX 350 is a high viscosity, high molecular weight, reactive polyamide resin, based on dimerized fatty acid and polyamines for curing of epoxy resin based formulations. For easier handling, ATUREX 350 is also available as a 70% solids solution in xylene and other solution.

FEATURES

- Good chemical resistance
- Excellent flexibility
- Outstanding adhesion
- High viscosity
- Good corrosion resistance

- Good water resistance
- Good color and light stability
- Long pot life

APPLICATIONS

- Surface coatings
- Castings
- Primer coatings
- Adhesive (2-pack)
- Potting
- Finishing cements

PROPERTIES	TEST METHOD	SPECIFICATION
Aspect	Visual	High viscosity, clear liquid
Amine Number, mg KOH/g	ISO 9702	200-240
Colour, Gardner	ISO 4630	<9
Viscosity, mPa.s, 75°C	ISO 3219	30000-40000
TYPICAL PROPERTIES		
H ⁺ active equivalent g/eq		196
Density at 20°C	ISO 1675	0.96
Flash point °C	ISO 2719	≥ 200
HANDLING & STORAGE	In unopened, original containers, several years at 2 - 40°C, (see Expiry date on original container)	
CN CODE	3908900000	
PACKAGING	net weight 190kg in litre light head steel drums	
HEALTH & SAFETY	Please refer to Material Safety Data Sheet	



Economic development zone, yichun, jiangxi, China.
Phone: +86 186 0795 0576 Tel: +86 795 3586166
Fax: +86 795 3586165 E-Mail: jackie@aturex.com
Web: www.aturex.com

