

PRODUCT DATA SHEET

Revision Date: 13/01

ATUREX® 455

Modified Cycloaliphatic Amine Adduct

It is a long pot life version of ATUREX 425.

FEATURES

- Cure at low temperatures under damp conditions
- Good film properties
- Excellent color and color stability
- Good adhesion and very good chemical resistance
- Good water resistance
- Range of cure times and pot lives
- Very good heat-cure performance

APPLICATIONS

- Solvent-free and high-solids coatings
- Two-pack epoxy printing inks
- Mortars
- Self-leveling flooring
- Water-wipe able tile grouts
And Lamination

PROPERTIES	TYPICAL QUALITY	SPECIFICATION
Specific Gravity, 25°C	1.03	1.03
Solids, %	-	-
AHEW	125	125
Use Level, phr	65	65
Gel Time, min/150g, 25°C	90	90
Thin Film Set Time, hr/25°C	9.0	9.0
Typical Cure Schedule	4 days	2-7 days at ambient
TYPICAL PROPERTIES		
Amine Value, mg KOH/g	245	230-260
Viscosity, mPa.s, 25°C	300	200-400
Color, Gardner	1	<2
HANDLING & STORAGE	In unopened, original containers at 2 - 40°C, (see Expiry date on original container)	
CN CODE	3908900000	
PACKAGING	In 210 liter tight head steel drums, net weight 190kg.	
HEALTH & SAFETY	Please refer to Material Safety Data Sheet	



Economic Development Zone, Yichun, Jiangxi, China.
Phone: +86 186 0795 0576 Tel: +86 795 3586166
Fax: +86 795 3586165 E-Mail: jackie@aturex.com
Web: www.aturex.com

Publication number 10086 – Revision Jan.2013

The information and statements herein are believed to be reliable, but not to be construed as a warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification.