

PRODUCT DATA SHEET

Revision Date: 13/01

ATUREX[®] 550

Benzene-soluble and General Polyamide Resin

ATUREX 550 belong to benzene -soluble polyamide resin. With new production process, the product can control the cost of production at the same time, further improve the technical indexes, performance is more stable. In the midrange polyamide resin, it belong to high cost performance

FEATURES

- Good stability
- Solvent release good
- Low temperature not gel
- Excellent gloss and adhesion

APPLICATIONS

- Gravure printing ink
- Paper 、 thin film printing ink
- Primer coatings
- Over-Printing varnish

PROPERTIES	TEST METHOD	SPECIFICATION
Aspect	Visual	Light yellow granular
Amine Number, mg KOH/g	ISO 9702	<5
Colour, Gardner	ISO 4630	<7
Viscosity, mPa.s, 75°C	ISO 3219	100-180
TYPICAL PROPERTIES		
Softening point°C		110±5
Acid value (maKOH/g)		<5
Freezing point °C	I	<7
HANDLING & STORAGE	In unopened, original containers, several years at 2 - 40°C, (see Expiry date on original container)	
CN CODE	3908900000	
PACKAGING	Paper and Plastic, net weight 25kg	
HEALTH & SAFETY	Please refer to Material Safety Data Sheet	



Economic development zone, yichun, jiangxi, China.
Phone: +86 186 0795 0576 Tel: +86 795 3586166
Fax: +86 795 3586165 E-Mail: jackie@aturex.com
Web: www.aturex.com